


Brand hansgrohe
 Art. Name **ShowerSelect Comfort E**
 Art. Nr. 15572000
 Surface Chrome

Thermostat for concealed installation for 2 functions




Product picture



Features

- 2 functions
- simultaneous use of several outlets
- comfortable turning on / off of outlets with large Select-paddle
- water flow control with stop function
- thermostat cartridge, Start/stop valve to operate the functions
- maximum flow rate at 1 bar: 12,7 l/min
- maximum flow rate at 3 bar: 22,7 l/min
- flow rate upper outlet: 22 l/min
- flow rate lower outlet: 22,7 l/min
- min. operating pressure: 1 bar
- max. operating pressure: 10 bar
- escutcheon can be aligned by +/- 3°
- easy installation due to pre-assembled function block
- handles always at the same height regardless of the installation depth of the basic set
- Safety stop at 40 °C
- temperature limitation adjustable
- the thermostat offers the possibility for thermal disinfection
- material button: metal
- material handles: metal
- connection type: basic set iBox universal 2 (# 01500180)
- thermostat is delivered with buttons Rain small, Rain large, hand shower, Waterfall, bath tub

Drawing



Technology



Certificates



Brand hansgrohe
 Art. Name **ShowerSelect Comfort E** Thermostat for concealed installation for 2 functions
 Art. Nr. 15572000
 Surface Chrome

Required parts

Product picture	Art. Name	Art. Nr.
	hansgrohe Basic set	01500180

Brand hansgrohe
 Art. Name **ShowerSelect Comfort E** Thermostat for concealed installation for 2 functions
 Art. Nr. 15572000
 Surface Chrome

Flow chart

